



2813 Belair Road • Suite 307 • Fallston, MD 21047
Phone: 410-877-0033 • Fax: 410-877-3177
www.xpressflooring.com

Quarry-Tek “Easy Cleaning”

Quarry-Tek is a seamless epoxy flooring system that has a non-porous surface. Although the flooring feels rough to the touch and appears to hold dirt, the dirt is only on the surface. Follow these “Easy Cleaning” instructions when cleaning your Quarry -Tek floor.

Step-By-Step

1. Hose down the floor with hot water.
2. Apply a mild soap (i.e. Dawn Liquid Detergent) to the floor.
3. Using a deck brush or scrub brush, mix the soap and water on the floor and allow the mixture to sit on the floor for several minutes.
4. Hose off the soapy mixture to the floor drains. (A power washer is excellent.)
5. Use a floor squeegee to move remaining water to floor drains. (Very important step.)

If floor drains are not available, follow steps 1, 2 and 3 above, and continue as follows:

3. Add more water to the floor as a rinse.
4. Use a shop vacuum to remove water.
5. If shop vacuum is not available, use a mop to absorb the water. Wring mop out often and dump waste water before the bucket is full.

Recommended soaps are mild, non-abrasive cleaners like Dawn Liquid Detergent. This product can be found at your local grocery or drug store.

NEVER USE any of the following products on your Quarry-Tek floor. These products will cause permanent damage to the floor surface which will make future cleaning more difficult.

Any Enzyme cleaners, Chlorine, MEK, Acetone, Methylene Chloride, Butyl, Delimer, Phosphoric Acid, Hypochlorite, Ajax, Comet, Spic 'n Span or any other type of abrasive cleaner.